

## CORRIGENDUM-5

NIT No- EdCIL/DES/IIMS/ICT/2023/01

Date-05-09-2023

Name:

**SUPPLYING, INSTALLATION, TESTING & COMMISSIONING OF IP-PBX, LAN, Wi-Fi, IP CCTV, BIOMETRIC ATTENDANCE SYSTEM, SERVER & STORAGE AT PROPOSED PERMANENT CAMPUS OF IIM SIRMAUR RAMPUR GHAT ROAD, PAONTA SAHIB DISTRICT SIRMAUR, HIMACHAL PRADESH - 173025**

The following corrigendum is made to the above tender.

S/N	Chapter No.	Page No.	Description as per Tender Documents/ Corrigendum	Modified Description
1	Local Area Network (LAN) including management Core Switch	104	Switch shall support VSS or equivalent features allows links that are physically connected to two different switch to appear as a single port channel	Removed
2			Switch should support minimum 18K ACLs, 16K Multicast and 32K IPv4, 16K IPv6 Routes.	Switch should support minimum 7K ACLs, 16K Multicast and 32K IPv4, 16K IPv6 Routes.
3			Switch should have 1) 48 x 1/10/25G ports 2) Atleast 5 x 40/100G ports populated with required 40G transceivers/DAC cables. 3) Out of 5x40/100G UL ports 1 No of 100 G ports with required transceivers to connect Core to Core switch	Switch should have 1) 48 x 1/10/25G ports 2) Atleast 6 x 40/100G ports populated with required 40G transceivers/DAC cables. 3) Out of 6 x 40/100G UL ports 1 No of 100 G ports with required transceivers to connect Core to Core switch
4	Technical Specification of NMS	113	Must provide centralized management that should be able to manage wired, wireless & security components of 3rd party OEM's.	Must provide management solution that should be able to manage wired, wireless & security components of 3rd party OEM's.
5			The NMS tool should provide a complete view of the devices that are monitored and managed by tool. It also allows end-	The NMS tool should provide a complete view of the devices that are monitored and managed by tool. It also allows end-

			end provisioning, management, monitoring, and maintenance operations for the devices. NMS tool should simplify network operations by providing zero-touch setup, centralized management of networks, historical data reporting, and troubleshooting for networks located around city or around the state.	end provisioning, management, monitoring, and maintenance operations for the devices. NMS tool should simplify network operations by providing zero-touch setup, historical data reporting, and troubleshooting for networks located around city or around the state.
6	CHAPTER-VI Marking Matrix	43 of 149	Documents Required:  Proof of PF/ESI Documents along with declaration and An Undertaking to be submitted by designated authority (Company Secretary) of the organization for the past three years.	Documents Required:  Proof of PF/ESI Documents along with declaration and An Undertaking to be submitted by designated authority (Company Secretary/Statutory Auditor/CA) of the organization for the past three years.
7	Data Center Technical Specification for Hyperconverged infrastructure (HCI)	93	15TB usable capacity to be configured with minimum data protection of RF2 or higher. The capacity should be absolute capacity without considering any data efficiency techniques as Data Deduplication, compression, erasure coding etc. Each node shall also be provided with 1.9 TB dedicated SSD drive as caching capacity. Bidder should not use dry sizing of 1.9 TB.	15TB usable capacity to be configured with minimum data protection of RF2 or higher. The capacity should be absolute capacity without considering any data efficiency techniques as Data Deduplication, compression, erasure coding etc. Each node shall also be provided with 1.6 TB dedicated SSD drive as caching capacity. Bidder should not use drive sizing of 1.9 TB for capacity.

Sd/-  
Chief General Manager (DES)  
EdCIL (India) Limited